

TL-2P

Translucent/Frosty PET

2 Side Printable

- Excellent water resistance and weatherability
- Excellent shade consistency
- Excellent matt and print sharpness
- Can do hot foiling for incorporating security seals and logos
- Writable surface for adding comments and signatures
- Good anti-static properties for trouble-free printing
- Dimensionally stable film suitable for thermal lamination
- Excellent Scuff and Scratch resistance properties

2 side pre-primed PET (Polyethylene Terephthalate) film suitable for Electrophotography/ Dry Toner and HP Indigo digital press.

Ideal for use in photo books, wedding albums and commercial applications such as Certificates, Visiting Cards, Menu Cards, Brochures, Premium Event Tickets and many more.

Specifications

BASE FILM	Polyester film (PET)
SURFACE FINISH	Matt
SHELF LIFE	Two years from the date of packing
AVAILABLE SIZES	320 X 460 (mm), 530 X 750 (mm)
RECOMMENDED STORAGE	20 - 25°C and 50% ± 5% (RH)

Typical Properties

PROPERTY		TEST METHOD	UNIT	VALUE	
THICKNESS		Internal Method	Micron	135	200
			Gauge	540	800
YIELD		Internal Method	m2/kg	5.32	3.57
			in2/lb	3740	2510
TENSILE STRENGTH	MD	ASTM D-882	kg/cm2	1200	1100
			kpsi	17.1	15.6
	TD	ASTM D-882	kg/cm2	1400	1200
			kpsi	19.9	17.1
ELONGATION AT BREAK	MD	ASTM D-882	%	140	150
	TD	ASTM D-882	%	120	130

MD: Machine direction TD: Transverse direction

The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.



01844 208308 info@gifproducts.co.uk www.gifproducts.co.uk

Graphic Image Films Ltd. Unit 5 Ridge Way • Crendon Industrial Park • Long Crendon • Buckinghamshire • HP18 9BF